

Univar USA Inc Material Safety Data Sheet

MSDS No:	CDS64835		
Version No:	001 2014-06-17		
Order No:			

Univar USA Inc., 17425 NE Union Hill Rd., Redmond WA 98052 (425) 889 3400

Emergency Assistance

For emergency assistance involving chemicals call Chemtrec - (800) 424-9300

Page **1** of **7**

COMPANY IDENTITY: PRODUCT IDENTITY: SDS DATE: 06/13/2014 Univar **METHANOL** ORIGINAL: 06/13/2014 SDS NUMBER:

CDS64835

SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements of the Global Harmonizing System.
THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) IMPORTANT: Read this SDS before handling & disposing of this product.
Pass this information on to employees, customers, & users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

PRODUCT IDENTITY: METHANOL

PRODUCT USES: Solvent, Deicer

SDS NUMBER: CDS64835 COMPANY IDENTITY: Univar COMPANY ADDRESS: 17425

17425 NE Union Hill Road


COMPANY CITY: Redmond, WA 98052

COMPANY PHONE: 1-425-889-3400 EMERGENCY PHONES: CHEMTREC: 1-800-424-9300 (USA) CANUTEC: 1-613-996-6666 (CANADA)

SECTION 2. HAZARDS IDENTIFICATION

DANGER!!

2.1 HAZARD STATEMENTS: (CAT = Hazard Category) (H200s) PHYSICAL: Flammable Liquids:
H225 HIGHLY FLAMMABLE LIQUID AND VAPOR.(CAT:2) H225 HIGHLY FLAMMABLE LIQUID AND VAPOR.(CAf:2)
(H300s) HEALTH: Acute Toxicity, Oral:
H301 TOXIC IF SWALLOWED.(CAT:3)
(H300s) HEALTH: Aspiration Hazard:
H304 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.(CAT:1)
(H300s) HEALTH: Acute Toxicity, Dermal:
H311 TOXIC IN CONTACT WITH SKIN.(CAT:3)
(H300s) HEALTH: Skin Corrosion/Irritation:
H315 CAUSES SKIN TRRITATION (CAT:2) H300S) HEALTH: SKIN CONTOSION/INTICACTOR.
H315 CAUSES SKIN IRRITATION.(CAT:2)
(H300S) HEALTH: Serious Eye Damage/Eye Irritation:
H318 CAUSES SERIOUS EYE DAMAGE.(CAT:1)
(H300S) HEALTH: Acute Toxicity, Inhalation: (H300s) HEALTH: Acute Toxicity, Inhalation:
H331 TOXIC IF INHALED.(CAT:3)
(H300s) HEALTH: Target Organ Toxicity, Single Exposure:
H335 MAY CAUSE RESPIRATORY IRRITATION.(CAT:3)
H336 MAY CAUSE DROWSINESS OR DIZZINESS.(CAT:3)
H370 CAUSES DAMAGE TO ORGANS.(CAT:1)
(H400s) ENVIRONMENT: Hazardous to Aquatic Environment, Acute:
H402 HARMFUL TO AQUATIC LIFE.(CAT:3)



2.2 PRECAUTIONARY STATEMENTS:

EXPOSURE PREVENTION: AVOID EXPOSURE OF ADOLESCENTS, CHILDREN! P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal P233 Keep container tightly closed.

P240

Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools. P241

P242

P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breath dust/fume/gas/mist/vapors/spray.
P262 Do not get in eyes, on skin, or on clothing.
P264 Wash with soap & water thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+350 IF ON SKIN: Gently wash with soap & water.
P304+340 IF INHALED: Remove victime to fresh air & keep at rest in a position comfortable for breathing.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present & easy to do - Continue rinsing.
P307+311 If exposed: Call a POISON CENTER or doctor/physician.
Rinse mouth.

P330 Rinse mouth.

If skin irritation occurs: Get medical advice/attention.
Remove/Take off immediately all contaminated clothing.
Wash contaminated clothing before reuse.
Store in a well-ventilated place. Keep container tightly closed. P332+313 P361 P363

P403+233

Page **2** of **7**

COMPANY IDENTITY: Univar PRODUCT IDENTITY: METHANOL SDS NUMBER: CDS64835

SDS DATE: 06/13/2014 ORIGINAL: 06/13/2014

SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION. SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

 MATERIAL
 CAS#
 EINECS#
 WT %

 Methanol
 67-56-1
 200-659-6
 100

TRACE COMPONENTS: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

SECTION 4. FIRST AID MEASURES

- 4.1 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE & CHRONIC: See Section 11 for symptoms/effects, acute & chronic.
- First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists, refer to Section 8 for specific personal protective equipment.
- 4.3 EYE CONTACT:

 If this product enters the eyes, check for and remove any contact lenses. Open eyes while under gently running water. Use sufficient force to open eyelids. "Roll" eyes to expose more surface. Minimum flushing is for 15 minutes. Seek immediate medical attention.
- 4.4 SKIN CONTACT:

 If the product contaminates the skin, immediately begin decontamination with running water. Minimum flushing is for 15 minutes. Remove contaminated clothing, taking care not to contaminate eyes. If skin becomes irritated and irritation persists, medical attention may be necessary. Wash contaminated clothing before reuse, discard contaminated shoes.
- 4.5 INHALATION:
 After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR). Seek immediate medical attention.
- 4.6 SWALLOWING:
 Do not induce vomiting. GET MEDICAL ATTENTION IMMEDIATELY. If person is fully conscious give 1 cup or 8 ounces of water. If medical advice is delayed and if an adult has swallowed several ounces of chemical, then give 3-4 ounces (1/3-1/2 cup) (90-120 ml) of hard liquor such as 80 proof whiskey. For children, give proportionally less liquor at a dose of 0.3 ounce (1 1/2 tsp) (8 ml) liquor for each 10 pounds of body weight, or 2 ml per kg body weight (for example: 1.2 ounce (2 1/3 tablespoon) for a 40 pound child or 36 ml for an 18 kg child).
- 4.7 NOTES TO PHYSICIAN:
 In cases where several ounces (60 100 ml) have been ingested, consider the use of ethanol and hemodialysis in the treatment. Consult standard literature for details of treatment. If ethanol is used, a therapeutically effective blood concentration in the range of 100 150 mg/dl may be achieved by a rapid loading dose followed by a continuous intravenous infusion.1 Consult standard literature for details of treatment. 4-Methyl pyrazole (Antizol TM) is an effective blocker of alcohol dehydrogenase and should be used in the treatment of ethylene glycol, di- or triethylene glycol, ethylene glycol butyl ether, or methanol intoxication if available. Fomepizol protocol (Brent, J. et al, New England Journal of Medicine, Feb 8, 2001, 344:6, p. 424-9): loading dose 15 mg/kg intravenously, follow by bolus dose of 10 mg/kg every 12 hours; after 48 hours, increase bolus dose to 15 mg/kg every 12 hours. Continue fomepizol until serum methanol, EG, DEG, or TEG are undetectable. The signs and symptoms of poisoning include anion gap metabolic acidosis, CNS depression, renal tubular injury, and possible late stage cranial nerve involvement. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. Maintain adequate ventilation and oxygenation of the patient. In severe poisoning, respiratory support with mechanical ventilation and positive end expiratory pressure may be required. Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably from an ophthalmologist. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighted against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

Page **3** of **7**

COMPANY IDENTITY: Univar SDS DATE: 06/13/2014
PRODUCT IDENTITY: METHANOL ORIGINAL: 06/13/2014
SDS NUMBER: CDS64835

CECTION E ETE

SECTION 5. FIRE FIGHTING MEASURES

- 5.1 FIRE & EXPLOSION PREVENTIVE MEASURES: NO open flames, NO sparks, & NO smoking. explosion-proof electrical equipment, lighting.
- 5.2 SUITABLE (& UNSUITABLE) EXTINGUISHING MEDIA:
 Use dry powder, alcohol foam, water in large amounts, carbon dioxide.
- 5.3 SPECIAL PROTECTIVE EQUIPMENT & PRECAUTIONS FOR FIRE FIGHTERS: Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots).
- 5.4 SPECIFIC HAZARDS OF CHEMICAL & HAZARDOUS COMBUSTION PRODUCTS:

 HIGHLY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE
 Isolate from oxidizers, heat, sparks, electric equipment & open flame.
 Closed containers may explode if exposed to extreme heat.
 Applying to hot surfaces requires special precautions.
 Empty container very hazardous! Continue all label precautions!
 Burns with nonluminous blue flame.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT & EMERGENCY PROCEDURES:
 EVACUATE DANGER AREA! Consult an expert! Vapors may ignite explosively & spread long distances. Prevent vapor buildup. Keep unprotected personnel away. Ventilate spill area. Remove all ignition sources. Use complete chemical protective suit with self-contained breathing apparatus.
- 6.2 ENVIRONMENTAL PRECAUTIONS: Keep from entering storm sewers and ditches which lead to waterways.
- 6.3 METHODS & MATERIAL FOR CONTAINMENT & CLEAN-UP: Stop spill at source. Dike and contain. Collect leaking liquid in sealable containers. Wash away remainder with plenty of water.

SECTION 7. HANDLING AND STORAGE

- 7.1 PRECAUTIONS FOR SAFE HANDLING:
 Isolate from oxidizers, heat, sparks, electric equipment & open flame.
 Use only with adequate ventilation. Avoid breathing of vapor or spray mist.
 Avoid contact with skin & eyes. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse.
 Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!
- 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
 Keep in fireproof surroundings. Keep separated from strong oxidants, food & feedstuffs.
 Keep cool. Do not store above 49 C/120 F. Keep container tightly closed
 & upright when not in use to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 EXPOSURE LIMITS:

 MATERIAL
 CAS#
 EINECS#
 TWA (OSHA)
 TLV (ACGIH)

 Methanol
 67-56-1
 200-659-6
 200 ppm S
 200 ppm S

MATERIAL CAS# EINECS# CEILING STEL(OSHA/ACGIH) HAP
Methanol 67-56-1 200-659-6 None Known 250 ppm Yes

Each component showing `Yes' under "HAP" is an EPA Hazardous Air Pollutant.

Page **4** of **7**

COMPANY IDENTITY: Univar SDS DATE: 06/13/2014
PRODUCT IDENTITY: METHANOL ORIGINAL: 06/13/2014
SDS NUMBER: CDS64835

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.2 APPROPRIATE ENGINEERING CONTROLS:

RESPIRATORY EXPOSURE CONTROLS
A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

VENTILATION
LOCAL EXHAUST: Necessary MECHANICAL (GENERAL): Acceptable SPECIAL: None OTHER: None Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

8.3 INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

PERSONAL PROTECTIONS:
Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse.

WORK & HYGIENIC PRACTICES:

Provide readily accessible eye wash stations & safety showers.
Wash at end of each workshift & before eating, smoking or using the toilet.
Promptly remove clothing that becomes contaminated. Destroy contaminated
leather articles. Launder or discard contaminated clothing.

SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

```
Liquid, Water-White
Alcohol
APPEARANCE:
ODOR:
ODOR THRESHOLD:
                                                                                                            Not Available
pH (Neutrality):
MELTING POINT/FREEZING POINT:
                                                                                                            Not Available
                                                                                                            Not Available
                                                                                                            63 63 63 C / 147 147 147 F
12 C / 54 F (TCC)
BOILING RANGE (IBP,50%, Dry Point):
BOILING RANGE (IBP,50%,Dry Point):
FLASH POINT (TEST METHOD):
EVAPORATION RATE (n-Butyl Acetate=1):
FLAMMABILITY CLASSIFICATION:
LOWER FLAMMABLE LIMIT IN AIR (% by vol):
UPPER FLAMMABLE LIMIT IN AIR (% by vol):
VAPOR PRESSURE (mm of Hg)@20 C
VAPOR DENSITY (air=1):
GRAVITY @ 68/68 F / 20/20 C:
DENSITY:
SPECIFIC GRAVITY (Water=1):
                                                                                                            1.9
                                                                                                            Class I B
7.3
                                                                                                            36.0
                                                                                                            97.0
                                                                                                            1.1
                                                                                                            0.794
       SPECIFIC GRAVITY (Water=1):
                                                                                                            0.795
       POUNDS/GALLON:
                                                                                                            6.622
WATER SOLUBILITY:
                                                                                                            Complete
PARTITION COEFFICIENT (n-Octane/Water): AUTO IGNITION TEMPERATURE:
                                                                                                            Not Available
                                                                                                            463 C / 867 F
DECOMPOSITION TEMPERATURE:
                                                                                                            Not Available
REFRACTIVE INDEX:
                                                                                                            1.328
REFRACTIVE INDEX:
TOTAL VOC'S (TVOC)*:
NONEXEMPT VOC'S (CVOC)*:
HAZARDOUS AIR POLLUTANTS (HAPS):
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C) 0.0
VISCOSITY @ 20 C (ASTM D445):
* Using CARB (California Air Resources Board Rules).
                                                                                                           100.0 Vol% / 792.0 g/L / 6.5 Lbs/Gal
100.0 Vol% / 792.0 g/L / 6.5 Lbs/Gal
99.6 Wt% / 792.0 g/L / 6.5 Lbs/Gal
                                                                                                            Not Available
```

SECTION 10. STABILITY & REACTIVITY

10.1 REACTIVITY & CHEMICAL STABILITY: Stable under normal conditions.

10.2 POSSIBILITY OF HAZARDOUS REACTIONS & CONDITIONS TO AVOID: Isolate from oxidizers, heat, sparks, electric equipment & open flame.

10.3 INCOMPATIBLE MATERIALS: Reacts violently with strong oxidants, causing fire & explosion hazard.

SDS DATE: 06/13/2014

ORIGINAL: 06/13/2014

Page **5** of **7**

COMPANY IDENTITY: Univar PRODUCT IDENTITY: METHANOL SDS NUMBER: CDS64835

SECTION 10. STABILITY & REACTIVITY (CONTINUED)

10.4 HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide from burning.

10.5 HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 ACUTE HAZARDS

11.11 EYE & SKIN CONTACT:
Primary irritation to skin, defatting, dermatitis.
Primary irritation to eyes, redness, tearing, blurred vision.
Liquid can cause eye irritation. Wash thoroughly after handling.

11.12 INHALATION:
Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful. Breathing vapor can cause irritation.
Acute overexposure can cause harm to affected organs by routes of entry. Repeated exposure over TLV can cause blindness.

11.13 SWALLOWING:

Can be fatal or cause blindness if swallowed. Cannot be made non-poisonous. POISON! Can cause irreversible nervous system damage & death. Harmful or fatal if swallowed. Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

11.2 SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing disorders of any target organs mentioned in this SDS can be aggravated by over-exposure by routes of entry to components of this product. Persons with these disorders should avoid use of this product.

11.3 CHRONIC HAZARDS

- 11.31 CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:
 This product has no carcinogens listed by IARC, NTP, NIOSH,
 OSHA or ACGIH, as of this date, greater or equal to 0.1%.
 Absorption thru skin may be harmful. Studies with laboratory animals indicate this product can cause damage to fetus.
 Depending on degree of exposure, periodic medical examination is indicated.
- 11.32 TARGET ORGANS: May cause damage to target organs, based on animal data.
- 11.33 IRRITANCY: Irritating to contaminated tissue.
- 11.34 SENSITIZATION: No component is known as a sensitizer.
- 11.35 MUTAGENICITY: No known reports of mutagenic effects in humans.
- 11.36 EMBRYOTOXICITY: No known reports of embryotoxic effects in humans.
- 11.37 TERATOGENICITY: No known reports of teratogenic effects in humans.
- 11.38 REPRODUCTIVE TOXICITY: No known reports of reproductive effects in humans.

A MUTAGEN is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate across generational lines. An EMBRYOTOXIN is a chemical which causes damage to a developing embryo (such as: within the first 8 weeks of pregnancy in humans), but the damage does not propagate across generational lines. A TERATOGEN is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A REPRODUCTIVE TOXIN is any substance which interferes in any way with the reproductive process.

Page **6** of **7**

COMPANY IDENTITY: PRODUCT IDENTITY: Univar METHANOL SDS NUMBER: CDS64835 SDS DATE: 06/13/2014 ORIGINAL: 06/13/2014

SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)

11.4 MAMMALIAN TOXICITY INFORMATION

MATERIAL	CAS#	EINECS#	LOWEST KNOWN LETHAL DOSE DATA LOWEST KNOWN LD50 (ORAL)
Methanol	67-56-1	200-659-6	1000.0 mg/kg(Man) LOWEST KNOWN LD50 (SKIN)
Methanol	67-56-1	200-659-6	20000.0 mg/kg (Rabbits)

SECTION 12. ECOLOGICAL INFORMATION

- 12.1 ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.
- 12.2 EFFECT OF MATERIAL ON PLANTS AND ANIMALS: This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.
- 12.3 EFFECT OF MATERIAL ON AQUATIC LIFE: The most sensitive known aquatic group to any component of this product is: Goldfish 250 ppm or mg/L (24 hour exposure).
 Keep out of sewers and natural water supplies.
- 12.4 MOBILITY IN SOIL This material is a mobile liquid.
- 12.5 DEGRADABILITY This product is partially biodegradable.
- 12.6 ACCUMULATION This product does not accumulate or biomagnify in the environment.

SECTION 13. DISPOSAL CONSIDERATIONS

The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirments of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers and liners may retain some product residues. Vapor from some product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal.

ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES. EPA CHARACTERISTIC: D001 The generation of waste should be avoided or minimized wherever possible.

SECTION 14. TRANSPORT INFORMATION

IF > 5018 LB / 2280 KG OF THIS PRODUCT IS IN 1 CONTAINER, IT EXCEEDS THE RQ OF METHANOL. "RQ" MUST BE PUT BEFORE THE DOT SHIPPING NAME.

MARINE POLLUTANT:

MAKINE POLLUTANT: NO
DOT/TDG SHIP NAME: UN1230, Methanol, 3, PG-II
DRUM LABEL: (FLAMMABLE LIQUID)
IATA / ICAO: UN1230, Methanol, 3, (6.1), PG-II
IMO / IMDG: UN1230, Methanol, 3, (6.1), PG-II
EMERGENCY RESPONSE GUIDEBOOK NUMBER: 131







SDS DATE: 06/13/2014

ORIGINAL: 06/13/2014

Page **7** of **7**

COMPANY IDENTITY: PRODUCT IDENTITY: Univar **METHANOL**

SDS NUMBER: CDS64835

SECTION 15. REGULATORY INFORMATION

15.1 EPA REGULATION:

SARA SECTION 311/312 HAZARDS: Acute Health, Fire

All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated <*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS *Methanol

67-56-1 200-659-6 90-100 (311.312 313 RQ(LBS) (311,312,313,RCRA)5000

Any release equal to or exceeding the RQ must be reported to the National Response Center (800-424-8802) and appropriate state and local regulatory agencies as described in 40 CFR 302.6 and 40 CFR 355.40 respectively. Failure to report may result in substantial civil and criminal penalties. State & local regulations may be more restrictive than federal regulations.

15.2 STATE REGULATIONS:

THIS PRODUCT MEETS REQUIREMENTS OF SOUTHERN CALIFORNIA AOMD RULE 443.1 & SIMILAR REGULATIONS

CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65):
This product contains the following chemical known to the State of California to cause reproductive toxicity: Methanol

15.3 INTERNATIONAL REGULATIONS

The identified components of this product are listed on the chemical inventories Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS), Japan (METI/CSCL, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC), Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

15.4 CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

B2: Flammable Liquid. D2B: Irritating to skin / eyes.

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all information required by the CPR.

SECTION 16. OTHER INFORMATION

16.1 HAZARD RATINGS: HEALTH (NFPA): 3, HEALTH (HMIS): 3, FLAMMABILITY: 3, PHYSICAL HAZARD: 0 (Personal Protection Rating to be supplied by user based on use conditions.) This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

16.2 EMPLOYEE TRAINING

See Section 2 for Risk & Safety Statements. Employees should be made aware of all hazards of this material (as stated in this SDS) before handling it.

16.3 SDS DATE: 06/13/2014

Univar USA Inc Material Safety Data Sheet

For Additional Information contact MSDS Coordinator during business hours, Pacific time: (425) 889-3400

Notice

Univar USA Inc. ("Univar") expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this MSDS as a product specification. For product specification information refer to a product specification sheet and/or a certificate of analysis. These can be obtained from your local Univar sales office.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Univar makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Univar's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process