

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

LA-CO Industries, Inc.

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)
Date of issue: 07/21/2015
Revision date: 10/29/2015

Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Marking.

1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.
1201 Pratt Boulevard
Elk Grove Village, IL. 60007-5746
Phone: (847) 956-7600
Fax: (847) 956-9885
E-mail: customer_service@laco.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification in accordance with the Globally Harmonized Standard

Not classified

2.2. Label elements

GHS-US labelling

No labelling applicable

2.3. Other hazards

2.4. Unknown acute toxicity (GHS US)

1.1 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
1.1 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
1.17 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	% (w/w)	GHS-US classification
aluminium powder (pyrophoric)	(CAS No) 7429-90-5	12.15 – 16.2 : Aluminum 19.56 – 26.08 : Silver	Pyr. Sol. 1, H250 Water-react. 2, H261
Carbon black	(CAS No) 1333-86-4	2.25 : 16 Black 0.91 – 1.42 : Black 0.24 : Gray	Carc. 2, H351
Silicon dioxide (cristobalite)	(CAS No) 14808-60-7	0 – 1.1 : Black 0 – 1.09 : Red, Black 0 – 0.96 : White 0 – 1.07 : Blue 0 – 1.06 : Green, Orange	Carc. 1A, H350

B Paintstik® MARKER 1 White, 1/2 Hex Blue, 1/2 Hex White, 1/2 Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Name	Product identifier	% (w/w)	GHS-US classification
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%)	(CAS No) 2786-76-7	0.12 : Pink 0.52 : Red	Skin Sens. 1, H317

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Wash with plenty of soap and water.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.
- First-aid measures after ingestion : Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : No particular fire or explosion hazard.
- Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

- Firefighting instructions : Keep upwind.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid creating or spreading dust.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Emergency procedures : Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Do not discharge into drains or the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Avoid generating dust. Sweep or shovel into suitable containers.

6.4. Reference to other sections

Section 8: personal protective equipment.

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Incompatible products : Strong oxidizers.
Prohibitions on mixed storage : Incompatible materials.
Storage area : Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

Marking.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

ACGIH	Not applicable	
OSHA	Not applicable	
Carbon black (1333-86-4)		
ACGIH	ACGIH TWA (mg/m ³)	3.5 mg/m ³
ACGIH	Remark (ACGIH)	Bronchitis
OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
Canada (Quebec)	VEMP (mg/m ³)	10 mg/m ³ (Fibres de carbone et de graphite; Poussière totale) 5 mg/m ³ (Fibres de carbone et de graphite; Poussière respirable) 3.5 mg/m ³
aluminium powder (pyrophoric) (7429-90-5)		
ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³
ACGIH	Remark (ACGIH)	Pneumoconiosis; LRT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Canada (Quebec)	VEMP (mg/m ³)	10 mg/m ³
Canada (Quebec)	Notations and remarks	(Métal)
Silicon dioxide (cristobalite) (14808-60-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³
ACGIH	Remark (ACGIH)	(respirable dust)
OSHA	OSHA PEL (TWA) (ppm)	250 mppcf
OSHA	Remark (OSHA)	(3) See Table Z-3.
Canada (Quebec)	VEMP (mg/m ³)	0.1 mg/m ³
Canada (Quebec)	Notations and remarks	(la poussière respirable), (C2)
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)		
ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

Appropriate engineering controls : Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Eyewash stations.
Personal protective equipment : Avoid all unnecessary exposure.
Hand protection : None under normal use.

B Paintstik® MARKER 1 White, 1/2 Hex Blue, 1/2 Hex White, 1/2 Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: None under normal use.
Other information	: Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: A solid crayon-like marker.
Colour	: Variable.
Odour	: Slight, vegetable oil.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: 66 °C
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 204 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 0 %
-------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization may occur.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Aldehydes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg
LC50 inhalation rat (mg/l)	> 4.6 mg/m ³ 4 h

aluminium powder (pyrophoric) (7429-90-5)	
LD50 oral rat	> 15900 mg/kg bodyweight

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
LD50 oral rat	> 15000 mg/kg
LC50 inhalation rat (mg/l)	> 1580 mg/m ³ 4 h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.

Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans, Inhalation of dust
National Toxicology Program (NTP) Status	Not listed in carcinogenicity class

Silicon dioxide (cristobalite) (14808-60-7)	
IARC group	1 - Carcinogenic to humans, Inhalation of dust

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Likely routes of exposure	: Inhalation;Skin and eye contact

SECTION 12: Ecological information

12.1 Toxicity

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
LC50 fish 1	> 500 mg/l 96 h
EC50 Daphnia 1	> 110 mg/l 48 h

12.2. Persistence and degradability

Carbon black (1333-86-4)	
Persistence and degradability	Not readily biodegradable.

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	0 % 28 d

12.3. Bioaccumulative potential

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
BCF fish 1	53 l/kg
Log Pow	1.28

12.4. Mobility in soil

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

12.5. Other adverse effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with DOT and TDG

Not considered a dangerous good for transport regulations

Proper Shipping Name (ADR) : Not applicable

Transport hazard class(es) (ADR) :

Transport by sea

Transport hazard class(es) (IMDG) :

Air transport

Transport hazard class(es) (IATA) :

SECTION 15: Regulatory information

15.1. US Federal regulations

Carbon black (1333-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

aluminium powder (pyrophoric) (7429-90-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Silicon dioxide (cristobalite) (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

aluminium powder (pyrophoric) (7429-90-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Silicon dioxide (cristobalite) (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

Carbon black (1333-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

aluminium powder (pyrophoric) (7429-90-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Silicon dioxide (cristobalite) (14808-60-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

National regulations

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).

All ingredients are listed in the Toxic Substances Control Act (TSCA).

All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

15.3. US State regulations

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

State or local regulations

The carbon black in this product is bound and is not respirable. California Prop. 65 warnings are not required.

Carbon black (1333-86-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	

Carbon black (1333-86-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

aluminium powder (pyrophoric) (7429-90-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

Silicon dioxide (cristobalite) (14808-60-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information


Indication of changes	: SECTION 15.
Data sources	: ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database . Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html .
Abbreviations and acronyms	: ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number. CLP: Classification, Labelling, Packaging. EC50: Environmental Concentration associated with a response by 50% of the test population. GHS: Globally Harmonized System (of Classification and Labeling of Chemicals). LD50: Lethal Dose for 50% of the test population. OSHA: Occupational Safety & Health Administration. PBT: Persistent, Bioaccumulative, Toxic. TWA: Time Weight Average. TSCA: Toxic Substances Control Act.
Other information	: None.

B Paintstik® MARKER 1 White, 1/2 Hex Blue, 1/2 Hex White, 1/2 Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
NFPA fire hazard : 1 - Must be preheated before ignition can occur.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Full text of H-statements:

Carc. 1A	Carcinogenicity, Category 1A
Carc. 2	Carcinogenicity, Category 2
Pyr. Sol. 1	Pyrophoric Solids, Category 1
Skin Sens. 1	Sensitisation — Skin, Category 1
Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2
H250	Catches fire spontaneously if exposed to air
H261	In contact with water releases flammable gases
H317	May cause an allergic skin reaction
H350	May cause cancer
H351	Suspected of causing cancer

SDS Prepared by: The Redstone Group, LLC
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43016
T 614-923-7472
www.redstonegrp.com

LACO NA GHS SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product