# LPS

# SAFETY DATA SHEET

# 1. Identification

Product identifier LPS® LST (Aerosol)

Other means of identification

Part Number 01916

Recommended use An industrial penetrant designed to penetrate rust and loosen seized bolts and other equipment

damaged by corrosion.

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer

Company name LPS Laboratories, a division of Illinois Tool Works, Inc.

**Address** 4647 Hugh Howell Rd.

Tucker, GA 30084

Country (U.S.A.)

Tel: +1 770-243-8800

In Case of Emergency 1-800-424-9300 (inside U.S.)

+001 703-527-3887 (outside U.S.)

Website www.lpslabs.com E-mail sds@lpslabs.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Compressed gas

Health hazards Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if

swallowed and enters airways.

**Precautionary statement** 

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Storage Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/122 °F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

## **Mixtures**

Chemical name	Common name and synonyms	CAS number	%	
Distillates Petroleum, Hydroteated		64742-47-8	90 - 100	
Light				

Material name: LPS® LST (Aerosol)
787 Version #: 01 Issue date: 07-18-2014

SDS US

Chemical name	Common name and synonyms	CAS number	%
Carbon Dioxide		124-38-9	1 - 5
Distillates Petroleum Hydrotreated Heavy		64742-54-7	< 1

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing

difficulties, oxygen may be necessary. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if **Eve contact** present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

> Call a physician or poison control center immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Ingestion

Dermatitis. Rash. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Call a POISON CENTER or doctor/physician if you feel unwell.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Powder. Alcohol resistant foam. Water. Water spray. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol. General fire hazards

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Use water spray to reduce vapors or divert vapor cloud drift. Scoop up used absorbent into drums or other appropriate container. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

SDS US

# 7. Handling and storage

# Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of the reach of children.

# 8. Exposure controls/personal protection

#### Occupational exposure limits

U.S. - OSHA

Components	Туре	Value	Form
Distillates Petroleum, Hydroteated Light (CAS 64742-47-8)	PEL	5 mg/m3	Oil mist
US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.10	000)	
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
,		5000 ppm	
ACGIH			
Components	Туре	Value	Form
Distillates Petroleum, Hydroteated Light (CAS 64742-47-8)	TWA	5 mg/m3	Oil mist
US. ACGIH Threshold Limit Values Components	s Type	Value	
		Value	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
US. NIOSH: Pocket Guide to Chem	nical Hazards		
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	

# Biological limit values Appropriate engineering

No biological exposure limits noted for the ingredient(s).

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

5000 ppm

# Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Chemical resistant gloves are recommended.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Not applicable.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** Liquid. Gas. Physical state **Form** Aerosol. Clear Color Odor Vanilla

**Odor threshold** Not available. pН Not applicable Melting point/freezing point Not established Initial boiling point and boiling 383 °F (195 °C)

range

Flash point 174.2 °F (79.0 °C) Tag Closed Cup

**Evaporation rate** < 0.7 BuAc Flammability (solid, gas) Flammable gas. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Not available.

(%)

Flammability limit - upper

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

< 0.1 mm Hg @ 20 °C Vapor pressure

Vapor density 4.7

Relative density Not available.

Solubility(ies)

< 0.1 % Solubility (water) **Partition coefficient** > 1

(n-octanol/water)

Not established **Auto-ignition temperature Decomposition temperature** Not established Viscosity Not established

Other information

Heat of combustion > 30 kJ/gPercent volatile 96 - 99 %

0.79 - 0.81 @ 20℃ Specific gravity

VOC (Weight %) 0 % per US State and Federal Consumer Product Regulations

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability** Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

Material name: LPS® LST (Aerosol)

# 11. Toxicological information

# Information on likely routes of exposure

Harmful if swallowed. May be fatal if swallowed and enters airways. Ingestion

Inhalation Prolonged inhalation may be harmful.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Irritating to eyes, respiratory system and skin. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Exposure may cause temporary irritation, redness, or discomfort.

Information on toxicological effects

Based on available data, the classification criteria are not met. Acute toxicity

Components **Species** Test Results

Distillates Petroleum Hydrotreated Heavy (CAS 64742-54-7)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

Rat LC50 > 2.5 mg/l

Oral

LD50 Rat > 2000 mg/kg

Distillates Petroleum, Hydroteated Light (CAS 64742-47-8)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Cat > 6.4 mg/lRat > 0.1 mg/l

Oral

> 5000 mg/kg LD50 Rat

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Based on available data, the classification criteria are not met. Reproductive toxicity

Specific target organ toxicity -

single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

**Aspiration hazard** May be fatal if swallowed and enters airways.

Prolonged inhalation may be harmful. **Chronic effects** 

12. Ecological information

**Ecotoxicity** Ecological injuries are not known or expected under normal use.

Material name: LPS® LST (Aerosol)

Components Species Test Results

Distillates Petroleum, Hydroteated Light (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 2.9 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability Not inherently biodegradable.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

LPS® LST (Aerosol) > 1

Mobility in soil Readily absorbed into soil.

Other adverse effects None known.

13. Disposal considerations

**Disposal instructions**Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code D003: Waste Reactive material

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

# 14. Transport information

DOT

UN number UN1950

**UN proper shipping name** Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not applicable.

**Environmental hazards** No **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only Allowed.

**IMDG** 

UN number UN1950

UN proper shipping name Transport hazard class(es) **AEROSOLS** 

Class 2

Material name: LPS® LST (Aerosol)
787 Version #: 01 Issue date: 07-18-2014

Subsidiary risk

Packing group

Not applicable.

**Environmental hazards** 

Marine pollutant

No

**EmS** F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. This substance/mixture is not intended to be transported in bulk.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



# 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

**Hazard categories** Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Material name: LPS® LST (Aerosol)

# Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

Inventory name

(SDWA)

#### **US** state regulations

#### **US. Massachusetts RTK - Substance List**

Carbon Dioxide (CAS 124-38-9)

# US. New Jersey Worker and Community Right-to-Know Act

Carbon Dioxide (CAS 124-38-9)

# US. Pennsylvania Worker and Community Right-to-Know Law

Carbon Dioxide (CAS 124-38-9)

#### **US. Rhode Island RTK**

Not regulated.

#### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

# **International Inventories**

Country(s) or region

Australian Inventory of Chemical Substances (AICS)	Yes
Domestic Substances List (DSL)	Yes
Non-Domestic Substances List (NDSL)	No
Inventory of Existing Chemical Substances in China (IECSC)	No
European Inventory of Existing Commercial Chemical Substances (EINECS)	No
European List of Notified Chemical Substances (ELINCS)	No
Inventory of Existing and New Chemical Substances (ENCS)	No
Existing Chemicals List (ECL)	No
New Zealand Inventory	No
Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
	Domestic Substances List (DSL) Non-Domestic Substances List (NDSL) Inventory of Existing Chemical Substances in China (IECSC) European Inventory of Existing Commercial Chemical Substances (EINECS) European List of Notified Chemical Substances (ELINCS) Inventory of Existing and New Chemical Substances (ENCS) Existing Chemicals List (ECL) New Zealand Inventory Philippine Inventory of Chemicals and Chemical Substances

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 07-18-2014

Version # 01

United States & Puerto Rico

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

Toxic Substances Control Act (TSCA) Inventory

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

On inventory (yes/no)\*

Yes