



PRODUCT: ETHANOL IDA GRADES (Industrial Denatured Alcohol)

(IDA) REVISION:3 DATED: 21/01/14 PAGE 1 OF 10

Product Name		Ethanol IDA Grades				
Alternative Name		Industrial Denatured Alcohol				
Product Grade		IMS/3 (05/02)				
Parameter	Units	IDA 95	IDA 96	IDA 99	IDA 100	Test Method
Alcohol Content	% volume at 20°C	95.1 max	96.1 max	99.5 max	100 max	OIML
Water Content		94.7 min	95.7 min	99.1 min	99.7 min	
Acidity	% mass	8.0 max	6.6 max	1.43 max	0.5 max	BS 2511
	% mass as acetic acid	0.003 max	0.003 max	0.003 max	0.003 max	B P Method
Total Carbonyls	(fixed)					
Appearance	% mass as acetaldehyde	0.1 max	0.1 max	0.1 max	0.1 max	BS 6392/3 ISO 1388/4
		Clear Colourless free from suspended matter	Clear Colourless free from suspended matter	Clear colourless free from suspended matter	Clear colourless free from suspended matter	BP Method
Colour	Hazen					
Miscibility With Water		20 max	20 max	20 max	20 max	B P Method BS6392/9
Residue On Evaporation		Complete	Complete	Complete	Complete	ISO 1388/2 BS 4524 ISO 759
	% mass	0.010 max	0.010 max	0.010 max	0.010 max	
PROPERTY	CONDITIONS	UNIT	VALUE			
Molecular mass			46.07			
Density	20°C	kg/litre (vacuo)	0.7894			
Coefficient of Cubical expansion	20°C	per °C	1.08 x 10 ⁻³			
Litres per Tonne	20°C	litres/T (in air)	1268.6			
Melting point		°C	-112.3			
Boiling point	1.013 bar	°C	78.32			
Change in boiling point	1.013 bar	°C/mbar	0.025			
Vapour pressure	20°C	m/bar	58.1			
Flammable limits						
	Upper	20°C	% volume	19.0		
	Lower	20°C	% volume	3.5		
Flash point	Abel closed cup	°C	12			
Auto ignition temperature		°C	365			
Specific heat (liquid)	20°C	kJ/kg°C	2.399			
Specific heat (vapour)	90°C	kJ/kg°C	1.70			
Latent heat						
(of fusion)		kJ/kg	104.3			
(of vaporisation)	78.3°C	kJ/kg	855.4			
Heat of combustion	20°C	Mj/kg	30.15			
Critical temperature		°C	240.77			
Critical pressure		bar	64			
Critical volume		m ³ /kg mole	0.1669			
Volume Resistivity	25°C	ohm.m	7.0 x 10 ³			
Thermal Conductivity	20°C	mW/m.°C	167.26			
Dielectric constant	°C		25.7			
Refractive index	20°C	n ²⁰ _D	1.3614			
Absolute viscosity	20°C	cP	1.22			
Solubility in water	20°C	g/kg	Complete			
water in solvent	20°C	g/kg	Complete			
Evaporation rate	20°C		3.4			
Relative to n-BuAc = 1						



PRODUCT: ETHANOL IDA GRADES (Industrial Denatured Alcohol)

(IDA) REVISION:3 DATED: 21/01/14 PAGE 2 OF 10

NOTES

Exclusion of Liability

Information contained in this publication is accurate to the best of the knowledge and belief of Tennants.

Any information or advice obtained from Tennants otherwise than by means of this publication and whether relating to Tennants materials or other materials, is also given in good faith. However, it remains at all times the responsibility of the customer to ensure that Tennants materials are suitable for the particular purpose intended.

Tennants accepts no liability whatsoever (except as otherwise provided by law) arising out of the use of information supplied, the application, adaptation or processing of the products described herein, the use of other materials in lieu of Tennants materials or the use of Tennants materials in conjunction with such other materials.

Health and Safety

A Material Safety Data Sheet has been issued describing the health, safety and environmental properties of this product, identifying the potential hazards and giving advice on the handling precautions and emergency procedures. This must be consulted fully before handling, storage and use.



PRODUCT: ETHANOL IDA GRADES (Industrial Denatured Alcohol)

(IDA) REVISION:3 DATED: 21/01/14 PAGE 3 OF 10

SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

1.1 Product Identifier

Product Name Ethanol Blend - IDA
HMRC Tariff Number 2207 20 00 90
REACH Registration Number 01-2119457610-43-XXXX/01-2119457610-43-XXXX

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s) Industrial use, raw material for pharmaceutical products, raw material for plastics additives, raw material for lubricants and lubricant additives
Uses advised against No information provided

1.3 Details of the supplier of the safety data sheet

Tennants Distribution Limited
Hazelbottom Road
Cheetham
Manchester
M8 0GR
Tel: 44(0)161 205 4454
Fax: 44(0) 161 203 4298
Email: msds@tennantsdistribution.com

1.4 Emergency telephone number

Tel: 44(0)844 335 0001 (24 hours)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

2.1.1 Regulation 1272/2008 (CLP)

Flammable liquids, Category 2
Eye irritation, Category 2, Eyes
Specific target organ toxicity - single exposure, Category 2

H225: Highly flammable liquid and vapour.
H319: Causes serious eye irritation.
H371: May cause damage to organs.

2.1.2 EEC Directive 67/548/EEC & Directive 1999/45/EC

Highly flammable R11: Highly flammable

2.2 Label elements

2.2.1 According to Regulation (EC) No. 1272/2008 (CLP).

Hazard Pictogram



Signal word(s) Danger.

Hazard statement(s)

H225: Highly flammable liquid and vapour.
H319: Causes serious eye irritation.
H371: May cause damage to organs..

Precautionary statement(s)

Prevention

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P243: Take precautionary measures against static discharge.

Response

P303+P361+P353: IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P309+P311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor/ physician.

Storage

P403+P235: Store in a well-ventilated place. Keep cool

2.3. Other hazards

Vapours may form explosive mixtures with air.
Vapours may spread long distances and ignite.
Irritating to eyes



PRODUCT: ETHANOL IDA GRADES (Industrial Denatured Alcohol)

(IDA) REVISION:3 DATED: 21/01/14 PAGE 4 OF 10

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Hazardous Components

Ethanol; ethyl alcohol

Content >=95 - <=100
REACH Registration number 01-2119457610-43-XXXX
CAS-No. 64-17-5
EC No. 200-578-6
Classification
(67/548/EEC) F; R11
(Regulation (EC) No. 1272/2008) Flam. Liq. 2; H225. Eye Irrit. 2; H319

Methanol

Content >=1 - <3
REACH Registration number 01-2119433307-44-XXXX
CAS-No. 67-56-1
EC No. 200-659-6
Classification
(67/548/EEC) F; R11 T; R23/24/25, R39/23/24/25
(Regulation (EC) No. 1272/2008) Flam. Liq. 2; H225. Acute Tox. 3; H301. Acute Tox. 3: H311.
Acute Tox. 3; H331. STOT SE 1: H370

Purchased components of the mixture without a registration number are pre-registered or excluded from REACH. To date the suppliers have sent us no information regarding a subsequent registration
For the full text of the R Phrases mentioned in this Section, see Section 16
For the full text of the H-Statements mentioned in this Section, see Section 16

4. FIRST AID MEASURES

4.1 Description of first aid measures

General Advice

Take off all contaminated clothing immediately

Inhalation

Move to fresh air

Skin contact

Wash off immediately with plenty of water

Eye contact

Immediately flush eye(s) with plenty of water. If eye irritation persists, consult a specialist

Ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. If swallowed, seek medical advice immediately and show this container or label.

4.2 Most important symptoms and effects, both acute and delayed

Risks: Irritant effect

4.3 Indication of any immediate medical attention and special treatment needed

Treatment: For specialist advise physicians should contact the Poisons Information Service

5. FIRE FIGHTING MEASURES

5.1 Extinguishing Media

Suitable extinguishing media: Water spray. Dry powder. Alcohol-resistant foam. Carbon dioxide (CO₂) in enclosed spaces
Unsuitable extinguishing media: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting: Do not use a solid water stream as it may scatter and spread fire. Flash back possible over considerable distance. When fighting fires in enclosed spaces: caution, danger of suffocation!

5.3 Advice for fire-fighters

Protective equipment for fire-fighters: Use personal protective equipment. Wear self-contained breathing apparatus for fire-fighting if necessary.
Further information: Cool containers / tanks with water spray. Use water spray to cool unopened containers. Do not allow run-off from fire fighting to enter drains or water courses. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition - No smoking



PRODUCT: ETHANOL IDA GRADES (Industrial Denatured Alcohol)

(IDA) REVISION:3 DATED: 21/01/14 PAGE 5 OF 10

6.2 Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration. Do not allow material to contaminate ground water system

6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13)

6.4 Reference to other sections

For personal protection see section 8

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on protection against fire and explosion: Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Use only explosion-proof equipment

Temperature class: T2

Fire-fighting class: Fires involving liquids or liquid containing substances. Also includes substances which become liquid at elevated temperatures

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a cool, well-ventilated place.

German storage class: 3 Flammable Liquids

7.3 Specific end use(s)

Consult the technical guidelines for the use of this substance/mixture.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
EtOH	64-17-5	TWA	1,000 ppm 1,920 mg/m ³	12 2011	EH40 WEL
Methanol	67-56-1	TWA	200 ppm 260 mg/m ³	12 2009	ECTLV
		TWA	200 ppm 266 mg/m ³	12 2011	EH40 WEL
		STEL	250 ppm 333 mg/m ³	12 2011	EH40 WEL
		TWA	200 ppm 260 mg/m ³	12 2009	ECTLV
		TWA	200 ppm 266 mg/m ³	12 2011	EH40 WEL
		STEL	250 ppm 333 mg/m ³	12 2011	EH40 WEL

DNEL

ethanol; ethyl alcohol

End Use: Workers Exposure routes: Inhalation. Potential health effects: Acute effects, Local effects. Value: 1900 mg/m³

End Use: Workers. Exposure routes: Skin contact. Potential health effects: Chronic effects. Value: 343 mg/kg

End Use: Workers. Exposure routes: Inhalation. Potential health effects: Chronic effects. Value: 950 mg/m³

End Use: Consumers. Exposure routes: Inhalation. Potential health effects: Acute effects, Local effects. Value: 950 mg/m³

End Use: Consumers. Exposure routes: Skin contact. Potential health effects: Chronic effects. Value: 206 mg/kg

End Use: Consumers. Exposure routes: Inhalation. Potential health effects: Chronic effects. Value: 114 mg/m³

End Use: Consumers. Exposure routes: Ingestion. Potential health effects: Chronic effects. Value: 87 mg/kg

methanol

End Use: Workers Exposure routes: Skin contact Potential health effects: Acute effects Value: 40 mg/kg

End Use: Workers Exposure routes: Inhalation Potential health effects: Acute effects Value: 260 mg/m³ 200 ppm

End Use: Workers Exposure routes: Inhalation Potential health effects: Acute effects, Local effects Value:260 mg/m³ 200



PRODUCT: ETHANOL IDA GRADES (Industrial Denatured Alcohol)

(IDA) REVISION:3 DATED: 21/01/14 PAGE 6 OF 10

<p>ppm End Use: Workers Exposure routes: Skin contact Potential health effects: Chronic effects Value: 40 mg/kg End Use: Workers Exposure routes: Inhalation Potential health effects: Chronic effects Value: 260 mg/m³ 200 ppm End Use: Workers. Exposure routes: Inhalation. Potential health effects: Chronic effects, Local effects Value: 260 mg/m³ 200 ppm End Use: Consumers. Exposure routes: Skin contact. Potential health effects: Acute effects. Value: 8 mg/kg End Use: Consumers. Exposure routes: Inhalation. Potential health effects: Acute effects. Value: 50 mg/m³ End Use: Consumers. Exposure routes: Ingestion. Potential health effects: Acute effects. Value: 8 mg/kg End Use: Consumers. Exposure routes: Inhalation. Potential health effects: Acute effects, Local effects Value: 50 mg/m³ End Use: Consumers. Exposure routes: Skin contact. Potential health effects: Chronic effects. Value: 8 mg/kg End Use: Consumers. Exposure routes: Inhalation. Potential health effects: Chronic effects. Value: 50 mg/m³ End Use: Consumers. Exposure routes: Ingestion. Potential health effects: Chronic effects. Value: 8 mg/kg End Use: Consumers. Exposure routes: Inhalation. Potential health effects: Chronic effects, Local effects Value: 50 mg/m³</p>
<p>Predicted No Effect Concentrations (PNEC): ethanol; ethyl alcohol Fresh water Value: 0.96 mg/l Marine water Value: 0.79 mg/l Sediment (Fresh water) Value: 3.6 mg/kg Soil Value: 0.63 mg/kg methanol Fresh water Value: 154 mg/l Marine water Value: 15.4 mg/l Sediment (Fresh water) Value: 570.4 mg/kg Soil Value: 23.5 mg/kg</p>
<p>8.2 Exposure controls</p>
<p>Appropriate engineering controls Provide sufficient air exchange and/or exhaust in work rooms</p>
<p>Respiratory protection No personal respiratory protective equipment normally required. In inadequately ventilated areas, where workplace limits are exceeded, where unpleasant odours exist or where aerosols are in use, or smoke and mist occur, use self-contained breathing apparatus or breathing apparatus with a type A filter or appropriate combined filter (e.g. where aerosols are in use, or smoke and mist occur, A-P2 or ABEK-P2), in compliance with EN 141</p>
<p>Hand protection The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other., Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time., Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Gloves suitable for permanent contact: Material: butyl-rubber. Break through time: >= 480 min. Material thickness: 0.5 mm. Material: Fluorkautschuk. Break through time: >= 480 min. Material thickness: 0.4 mm Gloves suitable for splash protection: Material: Polychloroprene. Break through time: >= 120 min. Material thickness: 0.5 mm Unsuitable gloves: Material: Natural rubber/natural latex, Nitrile rubber/nitrile latex</p>
<p>Eye protection Tightly fitting safety goggles</p>
<p>Hygiene measures Take off all contaminated clothing immediately</p>
<p>Protective measures Do not breathe vapours or spray mist</p>
<p>Environmental protection General advice: Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration. Do not allow material to contaminate ground water system</p>



PRODUCT: ETHANOL IDA GRADES (Industrial Denatured Alcohol)

(IDA) REVISION:3 DATED: 21/01/14 PAGE 7 OF 10

9. PHYSICAL AND CHEMICAL PROPERTIES	
9.1 Information on basic physical and chemical properties	
Appearance	Liquid
Colour	Colourless
Odour	Alcohol-like
Odour Threshold	No data available
pH	Not applicable
Melting Point/Range	ca. -114°C
Boiling Point/ Range	ca. 75 – 78°C
Flash Point	12°C ASTM D 56
Evaporation Rate	No data available
Lower Explosion Limit	ca. 3.5% (V)
Upper Explosion Limit	ca. 15% (V)
Vapour Pressure	ca. 58 hPa, 20°C
Relative Vapour Density	1.03, 20°C
Density	ca. 0.8 g/cm ³
Water Solubility	Completely miscible
Partition Coefficient: n-octanol/water	log Pow: -0.35, 20°C
Autoignition Temperature	363°C
Thermal Decomposition	Distils without decomposition at atmospheric pressure
Viscosity, Dynamic	1.19 mPas, 20°C
Explosive Properties	Not explosive
Oxidising Properties	No oxidising properties
9.2 Other information	
Refractive Index	1.361, ISO 5661
10. STABILITY AND REACTIVITY	
10.1 Reactivity Vapours may form explosive mixtures with air	
10.2 Chemical stability Stable under normal conditions	
10.3 Possibility of hazardous reactions Hazardous reactions: Vapours may form explosive mixture with air	
10.4 Conditions to avoid Heat, flame and sparks. Extremes of temperature and direct sunlight	
10.5 Incompatible materials Materials To Avoid: Alkali metals. Acetic anhydride	
10.6 Hazardous decomposition products None known	
11. TOXICOLOGICAL INFORMATION	
11.1 Information on toxicological effects Component: ethanol; ethyl alcohol Acute Oral Toxicity: LD50: > 2,000 mg/kg, rat, OECD Test Guideline 401, GLP: no, (literature value) Acute Inhalation Toxicity: LC50: > 20 mg/l, 4 h, mouse, (literature value) Acute Dermal Toxicity: LD50: > 2,000 mg/kg, rabbit, OECD Test Guideline 402, GLP: no, (literature value) Other Health Effects This substance has no evidence of carcinogenic properties.	
Skin corrosion/irritation rabbit, Result: not irritating, OECD Test Guideline 404, GLP: yes, (literature value)	
Serious eye damage/irritation rabbit, Result: irritating, OECD Test Guideline 405, (literature value)	
Respiratory or skin sensitisation Maximisation Test, guinea pig, Result: not sensitizing, OECD Test Guideline 406, GLP: yes, (literature value)	
Germ cell mutagenicity Genotoxicity in vitro: Ames test, Salmonella typhimurium, with and without, Result: not mutagenic, OECD Test Guideline 471, GLP: no, (literature value)	



PRODUCT: ETHANOL IDA GRADES (Industrial Denatured Alcohol)

(IDA) REVISION:3 DATED: 21/01/14 PAGE 8 OF 10

STOT – Repeated exposure

rat, Oral, Exposure time: 90-day, NOAEL: 1,730 mg/kg, LOAEL: 3,160 mg/kg

methanol

Acute oral toxicity: LD50: > 2,000 mg/kg, rat, GLP: no, (literature value)
Acute inhalation toxicity: LC50: > 20 mg/l, 4 h, rat, GLP: no, (literature value)
Acute dermal toxicity: LD50: > 2,000 mg/kg, rabbit, GLP: no, (literature value)
Skin corrosion/irritation: rabbit, Result: irritating, GLP: no, (literature value)
Serious eye damage/eye irritation: rabbit, Result: irritating, GLP: no, (literature value)
Respiratory or skin sensitisation: Maximisation Test, guinea pig, Result: not sensitizing, GLP: no, (literature value)
Germ cell mutagenicity
Genotoxicity in vitro: Ames test, Salmonella typhimurium, with and without, Result: not mutagenic, Mutagenicity (Salmonella typhimurium - reverse mutation assay), GLP: no, (literature value)

12. ECOLOGICAL INFORMATION

Ecotoxicity

The product is not expected to be hazardous to the environment

12.1 Toxicity

Components

ethanol; ethyl alcohol

Toxicity to fish: LC50: > 100 mg/l, 48 h, Leuciscus idus, static test, OECD Test Guideline 203, GLP: no, (literature value)

Toxicity to daphnia and other aquatic invertebrates: EC50: > 100 mg/l, 24 h, Daphnia magna, static test, OECD Test Guideline 202, GLP: yes, (literature value)

Toxicity to algae: EC50: > 100 mg/l, Chlorella pyrenoidosa, static test, OECD Test Guideline 201, GLP: no, (literature value)

methanol

Toxicity to fish: LC50: >100 mg/l, 96h, Salmo gairdneri, semi-static test, literature value)

Toxicity to daphnia and other aquatic invertebrates: EC50: > 100 mg/l, 48 h, Daphnia magna, static test, (literature value)

Toxicity to algae: EC50: > 100 mg/l, 8 d, Scenedesmus quadricauda, static test, (literature value)

12.2 Persistence and degradability

Components

ethanol; ethyl alcohol

Biodegradability: aerobic, > 70 %, Result: Readily biodegradable., Exposure time: 5 d, OECD Test Guideline 301 D, GLP: no, (literature value)

methanol

Biodegradability: aerobic, > 60 %, Result: Readily biodegradable., Exposure time: 5 d, activated sludge of a predominantly domestic sewage, OECD Test Guideline 301 D, GLP: no

12.3 Bio accumulative potential

Components

ethanol; ethyl alcohol

Bioaccumulation: No bioaccumulation is to be expected (log Pow <= 4).

methanol

Bioaccumulation: No bioaccumulation is to be expected (log Pow <= 4).

12.4 Mobility in soil

Components

ethanol; ethyl alcohol

Mobility: No information available

methanol

Mobility: No information available

12.5 Results of PBT and vPvB assessment

Components

ethanol; ethyl alcohol

Assessment: This substance is not considered to be persistent, bioaccumulating nor toxic (PBT)., This substance is not considered to be very persistent nor very bioaccumulating (vPvB).

methanol: This substance is not considered to be persistent, bioaccumulating nor toxic (PBT)., This substance is not considered to be very persistent nor very bioaccumulating (vPvB).

12.6 Other adverse effects

Components

ethanol; ethyl alcohol

Chemical Oxygen Demand (COD): ca. 1,700 mg/g, Directive 84/449/EEC, C.9, GLP: no data



PRODUCT: ETHANOL IDA GRADES (Industrial Denatured Alcohol)

(IDA) REVISION:3 DATED: 21/01/14 PAGE 9 OF 10

Additional ecological information: No data available	
methanol	
Additional ecological information: In the range of water solubility not toxic under test conditions	
13. DISPOSAL CONSIDERATIONS	
13.1 Waste treatment methods	
Product: Can be incinerated, when in compliance with local regulations	
Contaminated packaging: Contaminated packaging should be emptied optimally and after being suitably cleaned returned for re-use	
14. TRANSPORT INFORMATION	
14.1 UN No. ADR/RID/IMDG/IATA	1170
14.2 Proper Shipping Name ADR/RID/IMDG IATA	ETHANOL SOLUTION, ETHYL ALCOHOL, ETHANOL, ETHYL ALCOHOL SOLUTION ETHANOL
14.3 Transport Hazard Class ADR/RID/IMDG/IATA	3
14.4 Packing Group ADR Packing Group Classification Code Hazard Identification No. Labels Tunnel Restriction Code RID Classification Classification Code Hazard Identification No. Labels IMDG Packing Group Labels EmS Number IATA Packing Instruction (cargo aircraft) Packing Group Labels	 II F1 33 3 (D/E) II F1 33 3 II 3 F-E, S-D 364 II 3
14.5 Environmental hazards ADR/RID/IMDG/IATA Environmentally Hazardous	 No
14.6 Special precautions for users	No data
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	
Ship type: - Pollution category: Z	
15. REGULATORY INFORMATION	
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
Candidate List of Substances of Very High Concern for Authorisation	
This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).	
Major Accident Hazard List	
96/82/EC Highly flammable Quantity 1: 5,000 t Quantity 2: 50,000 t	
96/82/EC Methanol 26 Quantity 1: 500 t Quantity 2: 5,000 t	
Other Regulations	
Take note of Dir 94/33/EC on the protection of young people at work.	
15.2 Chemical safety assessment	
A Chemical Safety Assessment has been carried out for this substance	



PRODUCT: ETHANOL IDA GRADES (Industrial Denatured Alcohol)

(IDA) REVISION:3 DATED: 21/01/14 PAGE 10 OF 10

16. OTHER INFORMATION

Full text of R Phrases referred to under sections 2 and 3

R11: Highly flammable.

R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.

R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

Full text of H-Statements referred to under sections 2 and 3

H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H370: Causes damage to organs.

H371: May cause damage to organs.

Identified uses

Manufacture/Intermediate: Industrial uses: Uses of substances as such or in preparations at industrial sites

Distribution: Industrial uses: Uses of substances as such or in preparations at industrial sites

Formulation: Industrial uses: Uses of substances as such or in preparations at industrial sites

Use in non-spray applications: Industrial uses: Uses of substances as such or in preparations at industrial sites

Use in spray applications: Industrial uses: Uses of substances as such or in preparations at industrial sites

Use in non-spray applications: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Use in spray applications: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Domestic Fuel: Consumer uses: Private households (= general public = consumers)

Use in products (< 50g / event): Consumer uses: Private households (= general public = consumers)

Enclosed systems: Consumer uses: Private households (= general public = consumers)

Use in coatings and paints: Consumer uses: Private households (= general public = consumers)

Use in antifreeze, de-icing and screen wash products: Consumer uses: Private households (= general public = consumers)

Cleaning products: Consumer uses: Private households (= general public = consumers)

Use as laboratory agent: Industrial uses: Uses of substances as such or in preparations at industrial sites

Laboratory agent: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Heat transfer fluid or other functional fluid: Industrial uses: Uses of substances as such or in preparations at industrial sites

Heat transfer fluid or other functional fluid: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Source of key data used to compile the data sheet

Supplier information

Modifications from last revision

The Safety Data Sheets have been revised throughout in accordance with Regulation (EC) No. 1207/2006 and amendments

Date: 21/01/14

Copyright© Tennants Distribution Ltd (2014)

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU 3, SU8, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of bulk, large scale chemicals (including petroleum products), Manufacture of fine chemicals
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
Environmental Release Categories	: ERC1, ERC4, ERC6a: Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in manufacture of another substance (use of intermediates)

2.1 Contributing scenario controlling environmental exposure:

ERC1, ERC4, ERC6a: Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in manufacture of another substance (use of intermediates)

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Viscosity, dynamic	1.2 mPas at 20 °C

Amount used

Annual amount per site	: 400,000,000 kg
------------------------	------------------

Frequency and duration of use

Continuous exposure	: 350 days/year
---------------------	-----------------

Environment factors not influenced by risk management

Other data/Other information	: Receiving surface water flow is 18000 m3/d.
------------------------------	---

Other given operational conditions affecting environmental exposure

Emission or Release Factor: Air	: 70 %
Emission or Release Factor: Water	87 %

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Conditions and measures related to municipal sewage treatment plant

Effectiveness (of a measure) : 90 %
Sludge Treatment : Disposal, Recovery Methods

Conditions and measures related to external treatment of waste for disposal

Disposal methods : Can be incinerated, when in compliance with local regulations.

2.2 Contributing scenario controlling worker exposure:

PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use) : Liquid substance
Vapour pressure : 57.3 hPa

Amount used

Remarks : Not applicable.

Frequency and duration of use

Frequency of use : > 4 days/week
Frequency of use : > 240 days/year
Application duration : >4 h

Human factors not influenced by risk management

Dermal exposure : Palms of both hands (480 cm²)
Remarks : PROC1, PROC2
Dermal exposure : Both hands (960 cm²)
Remarks : PROC8a, PROC8b

Other operational conditions affecting workers exposure

Outdoor / Indoor : Outdoor
Other Operational Conditions affecting worker exposure : Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenario

General exposures

Risk Management Measures

No other specific measures identified.
Handle substance within a predominantly closed system provided with extract ventilation., Ensure material transfers are under containment or extract ventilation., Provide extraction ventilation at points where emissions occur. Wear suitable gloves tested to EN374. Use suitable eye protection.

3. Exposure estimation and reference to its source

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC1 ERC4 ERC6a	ECETOC TRA, EUSES		Fresh water		< 0.0001 mg/L	0.000028
			Marine water		< 0.0001 mg/L	0.000003
			Soil		0.0012 mg/kg dwt	0.00188

Health

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR
PROC1	ECETOC TRA, EUSES	Inhalation		0.01 ppm	0.00002
				0.0192 mg/m3	0.00002
		Skin contact		0.3429 mg/kg/day	0.002212
PROC2	ECETOC TRA, EUSES	Inhalation		10 ppm	0.020219
				19.2083 mg/m3	0.020219
		Skin contact		1.3714 mg/kg/day	0.008847
PROC8a	ECETOC TRA, EUSES	Inhalation		50 ppm	0.101097
				96.042 mg/m3	0.101097
		Skin contact		13.714 mg/kg/day	0.088479
PROC8b	ECETOC TRA, EUSES	Inhalation		50 ppm	0.101097
				96.042 mg/m3	0.101097
		Skin contact		6.8571 mg/kg/day	0.044239
PROC9	ECETOC TRA, EUSES	Inhalation		50 ppm	0.101097
				96.042 mg/m3	0.101097
		Skin contact		6.8571 mg/kg/day	0.044239
	ECETOC TRA, EUSES				

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU 3, SU8, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of bulk, large scale chemicals (including petroleum products), Manufacture of fine chemicals
Process categories	PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
Environmental Release Categories	: ERC2: Formulation of preparations

**2.1 Contributing scenario controlling environmental exposure:
ERC2: Formulation of preparations**

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Viscosity, dynamic	1.2 mPas at 20 °C

Amount used

Annual amount	75,000,000 kg
---------------	---------------

Frequency and duration of use

Continuous exposure	300 days/year
---------------------	---------------

Environment factors not influenced by risk management

Other data/Other information	: Receiving surface water flow is 18000 m3/d.
------------------------------	---

Conditions and measures related to municipal sewage treatment plant

Percentage removed from waste eater	: 90 %
-------------------------------------	--------

Conditions and measures related to external treatment of waste for disposal

Disposal methods	: Dispose of as hazardous waste in compliance with local and national regulations.
------------------	--

2.2 Contributing scenario controlling worker exposure:

PROC8a, PROC8b, PROC9: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities, Transfer of substance or

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Product characteristics

Concentration of the Substance in Mixture/Article Covers the percentage of the substance in the product up to 100 % (unless stated differently).
 Physical Form (at time of use) Liquid substance
 Vapour pressure 58.5 hPa
 Process Temperature 20 °C

Amount used

Remarks : Not applicable.

Frequency and duration of use

Frequency of use > 4 workdays/week
 Frequency of use 240 days/year
 Exposure duration >4 h

Human factors not influenced by risk management

Dermal exposure : Palms of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor / Indoor Outdoor
 Outdoor / Indoor Indoor
 Ventilation rate per hour 15
 Other Operational Conditions affecting worker exposure Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenario

Risk Management Measures

Wear suitable gloves (tested to EN374) and eye protection.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC2	ECETOC TRA		Fresh water		0.52 mg/L	0.108
			Marine water		0.0515 mg/L	0.013
			Soil		0.007 mg/kg dwt	0.00222

Health

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR
PROC8a	ECETOC TRA, EUSES	Inhalation		50 ppm	0.101097
				96.0417 mg/m ³	0.101097
		Skin contact		13.7143	0.088794

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

				mg/kg/day	
PROC8b	ECETOC TRA, EUSES	Inhalation		50 ppm	0.101097
				96.0417 mg/m3	0.101097
		Skin contact		13.7143 mg/kg/day	0.088794
	ECETOC TRA, EUSES	Inhalation		50 ppm	0.101097
				96.0417 mg/m3	0.101097
		Skin contact		13.7143 mg/kg/day	0.088794

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU 3, SU 10: Industrial uses: Uses of substances as such or in preparations at industrial sites, Formulation
Process categories	PROC3: Use in closed batch process (synthesis or formulation) PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation
Environmental Release Categories	: ERC2: Formulation of preparations

**2.1 Contributing scenario controlling environmental exposure:
 ERC2: Formulation of preparations**

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Viscosity, dynamic	1.2 mPas at 20 °C

Amount used

Annual amount	280,000,000 kg
---------------	----------------

Frequency and duration of use

Continuous exposure	: 300 days/year
---------------------	-----------------

Environment factors not influenced by risk management

Other data/Other information	: Receiving surface water flow is 18000 m3/d.
------------------------------	---

Conditions and measures related to municipal sewage treatment plant

Percentage removed from waste eater	: 90 %
Sludge Treatment	: Can be landfilled or incinerated, when in compliance with local regulations.

Conditions and measures related to external treatment of waste for disposal

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Disposal methods Dispose of as hazardous waste in compliance with local and national regulations.

2.2 Contributing scenario controlling worker exposure:
PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC14: Use in closed batch process (synthesis or formulation), Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact), Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Transfer of substance or preparation into small containers (dedicated filling line, including weighing), Production of preparations or articles by tableting, compression, extrusion, pelletisation

Product characteristics

Concentration of the Substance in Mixture/Article Covers the percentage of the substance in the product up to 100 % (unless stated differently).
 Physical Form (at time of use) Liquid substance
 Vapour pressure 57.3 hPa
 Process Temperature 20 °C

Amount used

Remarks Not applicable.

Frequency and duration of use

Frequency of use > 4 workdays/week
 Frequency of use 240 days/year

Human factors not influenced by risk management

Dermal exposure Palms of both hands (480 cm²)
 Remarks PROC3
 Dermal exposure Both hands (960 cm²)
 Remarks PROC8a, PROC8b

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor
 Ventilation rate per hour 15
 Other Operational Conditions affecting worker exposure Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenario

Risk Management Measures

Wear suitable gloves (tested to EN374) and eye protection.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC2	ECETOC TRA		Fresh water		0.185 mg/L	0.193
			Marine water		0.0186 mg/L	0.0235

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Soil 0.0117 0.0186
mg/kg_dwt

Health

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR
PROC3	ECETOC TRA, EUSES	Inhalation		25 ppm	0.050548
				48.0208 mg/m3	0.050548
		Skin contact		0.3429 mg/kg/day	0.002212
PROC5	ECETOC TRA, EUSES	Inhalation		50 ppm	0.101097
				96.0417 mg/m3	0.101097
		Skin contact		13.7143 mg/kg/day	0.088479
PROC8a	ECETOC TRA, EUSES	Inhalation		50 ppm	0.101097
				96.0417 mg/m3	0.101097
		Skin contact		13.7143 mg/kg/day	0.088479
PROC8b	ECETOC TRA, EUSES	Inhalation		50 ppm	0.101097
				96.0417 mg/m3	0.101097
				6.8571 mg/kg/day	0.044239
PROC9	ECETOC TRA, EUSES	Inhalation		50 ppm	0.101097
				96.0417 mg/m3	0.101097
		Skin contact		6.8571 mg/kg/day	0.044239
PROC14	ECETOC TRA, EUSES	Inhalation		50 ppm	0.101097
				96.0417 mg/m3	0.101097
		Skin contact		3.4826 mg/kg/day	0.02212

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROCIO: Roller application or brushing PROC13: Treatment of articles by dipping and pouring
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure:

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Viscosity, dynamic	1.2 mPas at 20 °C

Amount used

Annual amount	27,500,000 kg
---------------	---------------

Frequency and duration of use

Continuous exposure	300 days/year
---------------------	---------------

Environment factors not influenced by risk management

Other data/Other information	Receiving surface water flow is 18000 m3/d.
------------------------------	---

Conditions and measures related to municipal sewage treatment plant

Percentage removed from waste eater	: 90 %
Sludge Treatment	: Can be landfilled or incinerated, when in compliance with local regulations.

Conditions and measures related to external treatment of waste for disposal

Disposal methods	: Dispose of as hazardous waste in compliance with local and national regulations.
------------------	--

2.2 Contributing scenario controlling worker exposure:

PROCIO, PROC13: Roller application or brushing, Treatment of articles by dipping and pouring

Product characteristics

Concentration of the Substance in Mixture/Article	: Covers the percentage of the substance in the product up to 100 % (unless stated differently)
---	---

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Physical Form (at time of use) Liquid substance
 Vapour pressure 57.3 hPa
 Process Temperature 20 °C

Amount used

Remarks Not applicable.

Frequency and duration of use

Frequency of use > 4 workdays/week
 Frequency of use 240 days/year
 Application duration >4 h

Human factors not influenced by risk management

Dermal exposure Palms of both hands (480 cm²)
 Remarks PROC13
 Dermal exposure Both hands (960 cm²)
 Remarks PROCIO

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor
 Ventilation rate per hour 15
 Outdoor / Indoor Outdoor
 Other Operational Conditions Affecting worker exposure Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenario

Risk Management Measures

Wear suitable gloves (tested to EN374) and eye protection.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC4	ECETOC TRA		Fresh water		0.039 mg/L	0.0406
			Marine water		0.0039 mg/L	0.00494
			Soil		0.0091 mg/kg/day	0.0144

Health

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR
PROCIO	ECETOC TRA, EUSES	Inhalation		50 ppm	0.101097
				96.0417 mg/m ³	0.101097
		Skin contact		27.4286 mg/kg/day	0.176959
PROC13	ECETOC TRA, EUSES	Inhalation		50 ppm	0.101097
				96.0417 mg/m ³	0.101097

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

		Skin contact		13.7143 mg/kg/day	0.088479
--	--	--------------	--	----------------------	----------

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC7: Industrial spraying
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure:

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 25 %.
Viscosity, dynamic	1.2 mPas at 20 °C

Amount used

Annual amount	27,500,000 kg
---------------	---------------

Frequency and duration of use

Continuous exposure	: 300 days/year
---------------------	-----------------

Environment factors not influenced by risk management

Other data/Other information	: Receiving surface water flow is 18000 m ³ /d.
------------------------------	--

Other given operational conditions affecting environmental exposure

Emission or Release Factor: Air	: 70 %
Emission or Release Factor: Soil	: 70 %

Conditions and measures related to municipal sewage treatment plant

Percentage removed from waste eater	: 90 %
Sludge Treatment	: Can be landfilled or incinerated, when in compliance with local regulations.

Conditions and measures related to external treatment of waste for disposal

Disposal methods	: Dispose of as hazardous waste in compliance with local and national regulations.
------------------	--

2.2 Contributing scenario controlling worker exposure:

PROC7: Industrial spraying

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 25 %.
---	---

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Mixture/Article 25 %.
 Physical Form (at time of use) Liquid substance
 Vapour pressure 57.3 hPa
 Process Temperature 20 °C

Amount used

Remarks Not applicable.

Frequency and duration of use

Frequency of use > 4 workdays/week
 Frequency of use 240 days/year
 Exposure duration >4 h

Human factors not influenced by risk management

Dermal exposure : Two hands and forearms (1500 cm²)

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor
 Ventilation rate per hour 15
 Other Operational Conditions Affects a good basic standard of occupational hygiene is
 affecting worker exposure implemented.

Contributing Scenario

Risk Management Measures

Wear suitable respiratory protection (conforming to EN140 with Type A filter or better) and gloves (type EN374) if regular skin contact likely.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC4	ECETOC TRA		Fresh water		0.039 mg/L	0.0406
			Marine water		0.0039 mg/L	0.00494
			Soil		0.0091 mg/kg dwt	0.0144

Health

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR
PROC7	ECETOC TRA, EUSES	Inhalation		250 ppm	0.505483
				480.2083 mg/m ³	0.505483
		Skin contact		42.8571 mg/kg/day	0.276497
PROC7	ECETOC TRA, EUSES	Inhalation		125 ppm	0.025274
				24.0104 mg/m ³	0.025274
		Skin contact		2.1429	0.013825

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Sectors of end-use	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROCIO: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation PROC19: Hand-mixing with intimate contact and only PPE available
Environmental Release Categories	ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure:
ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Viscosity, dynamic	1.2 mPas at 20 °C

Amount used

Annual amount	10,000,000 kg
---------------	---------------

Frequency and duration of use

Continuous exposure	: 365 days/year
---------------------	-----------------

Environment factors not influenced by risk management

Other data/Other information	: Receiving surface water flow is 18000 m3/d.
------------------------------	---

Conditions and measures related to municipal sewage treatment plant

Effectiveness (of a measure)	: 90 %
Sludge Treatment	: Can be landfilled or incinerated, when in compliance with local regulations.
Remarks	: Ensure all waste water is collected and treated via a WWTP.

Conditions and measures related to external treatment of waste for disposal

Disposal methods	: Dispose of as hazardous waste in compliance with local and national regulations.
------------------	--

2.2 Contributing scenario controlling worker exposure:

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

PROCIO, PROC13, PROC14, PROC19: Roller application or brushing, Treatment of articles by dipping and pouring, Production of preparations or articles by tableting, compression, extrusion, pelletisation, Hand-mixing with intimate contact and only PPE available

Product characteristics

Concentration of the Substance in Mixture/Article Covers the percentage of the substance in the product up to 100 % (unless stated differently).
 Physical Form (at time of use) Liquid substance
 Vapour pressure 57.3 hPa
 Process Temperature 20 °C

Amount used

Remarks Not applicable.

Frequency and duration of use

Frequency of use > 4 workdays/week
 Frequency of use 240 days/year
 Frequency of use > 4 hours/day

Human factors not influenced by risk management

Dermal exposure Palms of both hands (480 cm²)
 Remarks PROC13, PROC14
 Dermal exposure Both hands (960 cm²)
 Remarks PROCIO
 Dermal exposure Two hands and forearms (1980 cm²)
 Remarks PROC19

Other operational conditions affecting workers exposure

Outdoor/Indoor : Indoor, Outdoor
 Other Operational Conditions affecting worker exposure : Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenario

PROC19

Risk Management Measures

: Avoid carrying out operation for more than 4 hours., , or:, Limit the substance content in the product to 25 %.
 Use suitable eye protection.Wear suitable gloves tested to EN374.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC8a ERC8d	ECETOC TRA		Fresh water		0.045 mg/L	0.0469
			Marine water		0.0044 mg/L	0.00557
			Soil		0.0003 mg/kg dwt	0.00476

Health

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR
PROCIO	ECETOC TRA, EUSES	Inhalation		100 ppm	0.202193
				192.0833 mg/m3	0.202193
		Skin contact		27.4286 mg/kg/day	0.176959
PROC13	ECETOC TRA, EUSES	Inhalation		100 ppm	0.202193
				192.0833 mg/m3	0.202193
		Skin contact		13.7143 mg/kg/day	0.088479
PROC14	ECETOC TRA, EUSES	Inhalation		100 ppm	0.202193
				192.0833 mg/m3	0.202193
		Skin contact		3.4286 mg/kg/day	0.02212
PROC19	ECETOC TRA, EUSES	Inhalation		100 ppm	0.202193
				192.0833 mg/m3	0.202193
		Skin contact		28.2857 mg/kg/day	0.182489
PROC19	ECETOC TRA, EUSES	Inhalation		60 ppm	0.121316
				115.25 mg/m3	0.121316
		Skin contact		141.4286 mg/kg/day	0.912443
PROC19	ECETOC TRA, EUSES	Inhalation		60 ppm	0.121316
				115.25 mg/m3	0.121316
		Skin contact		84.8572 mg/kg/day	0.547466
PROC19	ECETOC TRA, EUSES	Inhalation		20 ppm	0.040439
				38.4167 mg/m3	0.040439
		Skin contact		28.2857 mg/kg/day	0.182489
PROC19	ECETOC TRA, EUSES	Inhalation		36 ppm	0.072789
				69.15 mg/m3	0.072789
		Skin contact		84.8572 mg/kg/day	0.547466
PROC19	ECETOC TRA, EUSES	Inhalation		70 ppm	0.141535
				134.4583 mg/m3	0.141535
		Skin contact		141.4286 mg/kg/day	0.912443

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Sectors of end-use	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC11: Non industrial spraying
Environmental Release Categories	ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure:
ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

Product characteristics

Concentration of the Substance in Mixture/Article	:	Covers the percentage of the substance in the product up to 25 %.
Viscosity, dynamic	:	1.2 mPas at 20 °C

Amount used

Annual amount	10,000,000 kg
---------------	---------------

Frequency and duration of use

Continuous exposure	365 days/year
---------------------	---------------

Environment factors not influenced by risk management

Other data/Other information	Receiving surface water flow is 18000 m3/d.
------------------------------	---

Conditions and measures related to municipal sewage treatment plant

Effectiveness (of a measure)	:	90 %
Sludge Treatment	:	Can be landfilled or incinerated, when in compliance with local regulations.
Remarks	:	Ensure all waste water is collected and treated via a WWTP.

Conditions and measures related to external treatment of waste for disposal

Disposal methods	:	Dispose of as hazardous waste in compliance with local and national regulations.
------------------	---	--

2.2 Contributing scenario controlling worker exposure:

PROC11: Non industrial spraying

Product characteristics

Concentration of the Substance in Mixture/Article	:	Covers the percentage of the substance in the product up to 25 %.
Physical Form (at time of use)	:	Liquid substance

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Vapour pressure 57.3 hPa
 Process Temperature 20 °C

Amount used

Remarks : Not applicable.

Frequency and duration of use

Frequency of use > 4 workdays/week
 Frequency of use 300 days/year

Human factors not influenced by risk management

Dermal exposure : Two hands and forearms (1500 cm²)

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor, Outdoor
 Ventilation rate per hour 15

Contributing Scenario

Risk Management Measures

- : Avoid carrying out operation for more than 4 hours., , or:, Limit the substance content in the product to 5 %.
 Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Wear suitable gloves tested to EN374.
- : Avoid carrying out operation for more than 1 hour., , or:, Limit the substance content in the product to 25 %.
 Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Wear suitable gloves tested to EN374.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC8a ERC8d	ECETOC TRA		Fresh water		0.045 mg/L	0.0469
			Marine water		0.0044 mg/L	0.00557
			Soil		0.0003 mg/kg dwt	0.00476

Health

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR
PROC11	ECETOC TRA, EUSES	Inhalation		350 ppm	0.707675
				672.2917 mg/m ³	0.707675
		Skin contact		21.4286	0.138249

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

				mg/kg/day	
PROC11	ECETOC TRA, EUSES	Inhalation		300 ppm	0.606579
				576.25 mg/m3	0.606579
		Skin contact		64.2857 mg/kg/day	0.414747
PROC11	ECETOC TRA, EUSES	Inhalation		100 ppm	0.202193
				192.0833 mg/m3	0.202193
		Skin contact		21.4286 mg/kg/day	0.138249
PROC11	ECETOC TRA, EUSES	Inhalation		180 ppm	0.363947
				345.75 mg/m3	0.363947
		Skin contact		21.4286 mg/kg/day	0.138249
PROC11	ECETOC TRA, EUSES	Inhalation		100 ppm	0.202193
				192.0833 mg/m3	0.202193
		Skin contact		2.1429 mg/kg/day	0.013825
PROC11	ECETOC TRA, EUSES	Inhalation		350 ppm	0.707675
				672.2917 mg/m3	0.707675
		Skin contact		21.4286 mg/kg/day	0.138249

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Sectors of end-use	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC13: Fuels
Environmental Release Categories	ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure:

ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Viscosity, dynamic	1.2 mPas at 20 °C

Amount used

Annual amount	10,000,000 kg
---------------	---------------

Frequency and duration of use

Continuous exposure	365 days/year
---------------------	---------------

Environment factors not influenced by risk management

Other data/Other information	Receiving surface water flow is 18000 m3/d.
------------------------------	---

2.2 Contributing scenario controlling consumer exposure for: PC13: Fuels

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use)	Liquid substance
Vapour pressure	57.3 hPa
Process Temperature	20 °C

Amount used

Amount used per event	1 l
-----------------------	-----

Frequency and duration of use

Frequency of use	: 1 days/week
Exposure duration	: 5 min

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Other given operational conditions affecting consumers exposure

Outdoor/Indoor : Indoor, Outdoor

Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)

Application Route : Consumer use
 Consumer Measures : No specific measures identified., Use suitable eye protection.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC8a	ECETOC TRA		Fresh water		0.0447 mg/L	0.025
			Marine water		0.0044 mg/L	0.0043
			Soil		0.0003 mg/kg dwt	0.0433
ERC8d	ECETOC TRA		Fresh water		0.0447 mg/L	0.025
			Marine water		0.0044 mg/L	0.0043
			Soil		0.0003 mg/kg dwt	0.0043

Health

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	: SU 21: Consumer uses: Private households (= general public = consumers)
Sectors of end-use	: SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC1: Adhesives, sealants PC3: Air care products PC8: Biocidal products (e.g. Disinfectants, pest control) PC12: Fertilizers PC14: Metal surface treatment products, including galvanic and electroplating products PC15: Non-metal-surface treatment products PC18: Ink and toners PC23: Leather tanning, dye, finishing, impregnation and care products PC24: Lubricants, greases, release products PC27: Plant protection products PC28: Perfumes, fragrances PC30: Photo-chemicals PC31: Polishes and wax blends PC34: Textile dyes, finishing and impregnating products; including bleaches and other processing aids PC39: Cosmetics, personal care products
Environmental Release Categories	: ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure:

ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Viscosity, dynamic	1.2 mPas at 20 °C

Amount used

Annual amount	10,000,000 kg
---------------	---------------

Frequency and duration of use

Continuous exposure	365 days/year
---------------------	---------------

Environment factors not influenced by risk management

Other data/Other information	: Receiving surface water flow is 18000 m3/d.
------------------------------	---

Conditions and measures related to municipal sewage treatment plant

Percentage removed from waste	: 90 %
-------------------------------	--------

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

eater
 Sludge Treatment : Can be landfilled or incinerated, when in compliance with local regulations.

Conditions and measures related to external treatment of waste for disposal

Waste treatment : No specific measures identified.

Conditions and measures related to external recovery of waste

Remarks : No specific measures identified.

2.2 Contributing scenario controlling consumer exposure for: PC1, PC3, PC8, PC12, PC14, PC15, PC18, PC23, PC24, PC27, PC28, PC30, PC31, PC34, PC39: Adhesives, sealants, Air care products, Biocidal products (e.g. Disinfectants, pest control), Fertilizers, Metal surface treatment products, including galvanic and electroplating products, Non-metal-surface treatment products, Ink and toners, Leather tanning, dye, finishing, impregnation and care products, Lubricants, greases, release products, Plant protection products, Perfumes, fragrances, Photo-chemicals, Polishes and wax blends, Textile dyes, finishing and impregnating products; including bleaches and other processing aids, Cosmetics, personal care products

Product characteristics

Concentration of the Substance in Mixture/Article : Covers percentage substance in the product up to 1 %., PC24, PC31
 Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 5%., PC5, PC10, PC22, PC23, PC27, PC30, PC34
 Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 25%., PC1, PC8, PC14, PC15, PC18
 Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently)., PC3, PC28
 Physical Form (at time of use) : Liquid substance
 Vapour pressure : 57.3 hPa
 Process Temperature : 20 °C

Amount used

Amount used per event : 0.05 kg
 Remarks : PC24, PC31
 Amount used per event : 0.05 kg
 Remarks : PC5, PC10, PC22, PC23, PC27, PC30, PC34
 Amount used per event : 0.05 kg
 Remarks : PC1, PC8, PC14, PC15, PC18
 Amount used per event : 0.01 kg
 Remarks : PC3, PC28

Frequency and duration of use

Frequency of use : 365 days/year
 Exposure duration : 4 h

Other given operational conditions affecting consumers exposure

Outdoor/Indoor : Indoor
 Room size : 20 m3
 Outdoor/Indoor : Outdoor

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC8a ERC8d	ECETOC TRA		Fresh water		0.0447 mg/L	0.0466
			Marine water		0.0044 mg/L	0.00557
			Soil		0.0003 mg/kg dwt	0.000476

Health

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Sectors of end-use	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC16: Heat transfer fluids PC17: Hydraulic fluids
Environmental Release Categories	ERC9a, ERC9b: Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure:

ERC9a, ERC9b: Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Viscosity, dynamic	1.2 mPas at 20 °C

Amount used

Annual amount	10,000,000 kg
---------------	---------------

Frequency and duration of use

Continuous exposure	365 days/year
---------------------	---------------

Environment factors not influenced by risk management

Other data/Other information	Receiving surface water flow is 18000 m3/d.
------------------------------	---

2.2 Contributing scenario controlling consumer exposure for: PC16, PC17: Heat transfer fluids, Hydraulic fluids

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use)	Liquid substance
Vapour pressure	57.3 hPa
Process Temperature	20 °C

Amount used

Remarks	Not applicable.
---------	-----------------

Frequency and duration of use

Frequency of use	1 - 5 days/year
------------------	-----------------

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)

Application Route : Consumer use
 Consumer Measures : Use suitable eye protection.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC9a ERC9b	ECETOC TRA		Fresh water		0.0155 mg/L	0.0161
			Marine water		0.0014 mg/L	0.00184
			Soil		0.0001 mg/kg dwt	0.000206

Health

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups : **SU 21:** Consumer uses: Private households (= general public = consumers)
Sectors of end-use : **SU 21:** Consumer uses: Private households (= general public = consumers)
Chemical product category : **PC9a:** Coatings and paints, thinners, paint removers
PC9c: Finger paints
Environmental Release Categories : **ERC8a, ERC8d:** Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure:

ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 25 %.
Viscosity, dynamic : 1.2 mPas at 20 °C

Amount used

Annual amount : 10,000,000 kg

Frequency and duration of use

Continuous exposure : 365 days/year

Environment factors not influenced by risk management

Other data/Other information : Receiving surface water flow is 18000 m3/d.

Conditions and measures related to municipal sewage treatment plant

Percentage removed from waste eater : 90 %
Sludge Treatment : Can be landfilled or incinerated, when in compliance with local regulations.

Conditions and measures related to external treatment of waste for disposal

Waste treatment : No specific measures identified.

2.2 Contributing scenario controlling consumer exposure for: PC9a, PC9c: Coatings and paints, thinners, paint removers, Finger paints

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 25 %.
Physical Form (at time of use) : Liquid substance
Vapour pressure : 57.3 hPa

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Process Temperature : 20 °C

Amount used

Amount used per event : 0.250 kg

Frequency and duration of use

Frequency of use : 1 - 5 days/year

Exposure duration : 20-60 min

Human factors not influenced by risk management

Dermal exposure : Covers skin contact area up to 428.00 cm2

Other given operational conditions affecting consumers exposure

Outdoor/Indoor : Indoor

Room size : 20 m3

Outdoor/Indoor : Outdoor

Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)

Application Route : Consumer use

Consumer Measures : Ensure doors and windows are opened.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC8a ERC8d	ECETOC TRA		Fresh water		0.0447 mg/L	0.0466
			Marine water		0.0044 mg/L	0.00557
			Soil		0.0003 mg/kg dwt	0.000476

Health

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Sectors of end-use	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC4: Anti-Freeze and de-icing products
Environmental Release Categories	ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure:

ERC8d: Wide dispersive outdoor use of processing aids in open systems

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Viscosity, dynamic	1.2 mPas at 20 °C

Amount used

Annual amount	125,000,000 kg
---------------	----------------

Frequency and duration of use

Continuous exposure	365 days/year
---------------------	---------------

Environment factors not influenced by risk management

Other data/Other information	: Receiving surface water flow is 18000 m3/d.
------------------------------	---

Conditions and measures related to municipal sewage treatment plant

Percentage removed from waste eater	: 90 %
Sludge Treatment	: Can be landfilled or incinerated, when in compliance with local regulations.

Conditions and measures related to external treatment of waste for disposal

Remarks	: Use suitable eye protection.
---------	--------------------------------

2.2 Contributing scenario controlling consumer exposure for: PC4: Anti-Freeze and de-icing products

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use)	Liquid substance
Vapour pressure	57.3 hPa
Process Temperature	20 °C

Amount used

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Amount used per event : 0.05 kg

Frequency and duration of use

Frequency of use : 50 days/year
 Exposure duration : < 5 min

Human factors not influenced by risk management

Dermal exposure : Covers skin contact area up to 214.40 cm²

Other given operational conditions affecting consumers exposure

Outdoor/Indoor : Indoor, Outdoor

Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)

Consumer Measures : No specific measures identified.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC8d	ECETOC TRA		Fresh water		0.014 mg/L	0.0146
			Marine water		0.0013 mg/L	0.00165
			Soil		0.0001 mg/kg dwt	0.000206

Health

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups : **SU 21:** Consumer uses: Private households (= general public = consumers)
 Sectors of end-use : **SU 21:** Consumer uses: Private households (= general public = consumers)
 Chemical product category : **PC35:** Washing and cleaning products (including solvent based products)
 Environmental Release Categories : **ERC8a, ERC8d:** Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure:

ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 25 %.
 Viscosity, dynamic : 1.2 mPas at 20 °C

Amount used

Annual amount : 40,000,000 kg

Frequency and duration of use

Continuous exposure : 365 days/year

Environment factors not influenced by risk management

Other data/Other information : Receiving surface water flow is 18000 m3/d.

Conditions and measures related to municipal sewage treatment plant

Percentage removed from waste eater : 90 %
 Sludge Treatment : Can be landfilled or incinerated, when in compliance with local regulations.

2.2 Contributing scenario controlling consumer exposure for: PC35: Washing and cleaning products (including solvent based products)

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 5%.
 Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 25 %.
 Physical Form (at time of use) : Liquid substance
 VaDour Dressure : 57.3 hPa

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Process Temperature : 20 °C

Amount used

Amount used per event : 0.250 kg

Frequency and duration of use

Frequency of use : 365 hours/day

Exposure duration : 15 min -1 h

Other given operational conditions affecting consumers exposure

Outdoor/Indoor : Indoor, Outdoor

Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)

Application Route : Consumer use

Consumer Measures : No specific measures identified.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC8a ERC8d	ECETOC TRA		Fresh water		0.0818 mg/L	0.0852
			Marine water		0.008 mg/L	0.0102
			Soil		0.0004 mg/kg dwt	0.000716

Health

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC15: Use as laboratory reagent
Environmental Release Categories	ERC2, ERC4, ERC8a: Formulation of preparations, Industrial use of processing aids in processes and products, not becoming part of articles, Wide dispersive indoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure:

ERC2, ERC4, ERC8a: Formulation of preparations, Industrial use of processing aids in processes and products, not becoming part of articles, Wide dispersive indoor use of processing aids in open systems

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Viscosity, dynamic	1.2 mPas at 20 °C

Amount used

Annual amount	5,000,000 kg
---------------	--------------

Frequency and duration of use

Continuous exposure	300 days/year
---------------------	---------------

Environment factors not influenced by risk management

Other data/Other information	: Receiving surface water flow is 18000 m3/d.
------------------------------	---

Conditions and measures related to municipal sewage treatment plant

Percentage removed from waste eater	: 90 %
Sludge Treatment	: Can be landfilled or incinerated, when in compliance with local regulations.
Remarks	: Ensure all waste water is collected and treated via a WWTP.

2.2 Contributing scenario controlling worker exposure:

PROC15: Use as laboratory reagent

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use)	Liquid substance

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Vapour pressure 57.3 hPa
 Process Temperature 20 °C

Amount used

Remarks Not applicable.

Frequency and duration of use

Frequency of use > 4 workdays/week
 Frequency of use 240 days/year
 Exposure duration 1 - 4 h

Human factors not influenced by risk management

Dermal exposure : Palm of one hand (240 cm²)

Other operational conditions affecting workers exposure

Outdoor/Indoor : Indoor
 Other Operational Conditions : Assumes a good basic standard of occupational hygiene is affecting worker exposure implemented.

Contributing Scenario

Laboratory activities

Risk Management Measures

: No specific measures identified. Use suitable eye protection.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC2 ERC4 ERC8a	ECETOC TRA		Fresh water		0.027 mg/L	0.0281
			Marine water		0.0027 mg/L	0.00342
			Soil		0.0002 mg/kg dwt	0.000317

Health

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR
PROC15	ECETOC TRA, EUSES	Inhalation		10 ppm	0.020219
				19.2083 mg/m ³	0.020219
		Skin contact		0.3429 mg/kg/day	0.002212
PROC15	ECETOC TRA, EUSES	Inhalation		10 ppm	0.020219
				19.2083 mg/m ³	0.020219
		Skin contact		0.3429 mg/kg/day	0.002212

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Sectors of end-use	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC15: Use as laboratory reagent
Environmental Release Categories	ERC2, ERC4, ERC8a: Formulation of preparations, Industrial use of processing aids in processes and products, not becoming part of articles, Wide dispersive indoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure:

ERC2, ERC4, ERC8a: Formulation of preparations, Industrial use of processing aids in processes and products, not becoming part of articles, Wide dispersive indoor use of processing aids in open systems

Product characteristics

Concentration of the Substance in Mixture/Article	:	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Viscosity, dynamic	:	1.2 mPas at 20 °C

Amount used

Annual amount	5,000,000 kg
---------------	--------------

Frequency and duration of use

Continuous exposure	300 days/year
---------------------	---------------

Environment factors not influenced by risk management

Other data/Other information	Receiving surface water flow is 18000 m3/d.
------------------------------	---

Conditions and measures related to municipal sewage treatment plant

Percentage removed from waste eater	:	90 %
Sludge Treatment	:	Can be landfilled or incinerated, when in compliance with local regulations.
Remarks	:	Ensure all waste water is collected and treated via a WWTP.

2.2 Contributing scenario controlling worker exposure:

PROC15: Use as laboratory reagent

Product characteristics

Concentration of the Substance in Mixture/Article	:	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use)	:	Liquid substance

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Vapour pressure 57.3 hPa
 Process Temperature 20 °C

Amount used

Remarks Not applicable.

Frequency and duration of use

Frequency of use > 4 workdays/week
 Frequency of use 240 days/year
 Exposure duration 1 - 4 h

Human factors not influenced by risk management

Dermal exposure : Palm of one hand (240 cm²)

Other operational conditions affecting workers exposure

Outdoor/Indoor : Indoor
 Other Operational Conditions : Assumes a good basic standard of occupational hygiene is affecting worker exposure implemented.

Contributing Scenario

Laboratory activities

Risk Management Measures

: No specific measures identified. Use suitable eye protection.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC2 ERC4 ERC8a	ECETOC TRA		Fresh water		0.027 mg/L	0.0281
			Marine water		0.0027 mg/L	0.00342
			Soil		0.0002 mg/kg dwt	0.000317

Health

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR
PROC15	ECETOC TRA, EUSES	Inhalation		10 ppm	0.020219
				19.2083 mg/m ³	0.020219
		Skin contact		0.3429 mg/kg/day	0.002212
PROC15	ECETOC TRA, EUSES	Inhalation		10 ppm	0.020219
				19.2083 mg/m ³	0.020219
		Skin contact		0.3429 mg/kg/day	0.002212

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems
Environmental Release Categories	ERC7, ERC9a, ERC9b: Industrial use of substances in closed systems, Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure:

ERC7, ERC9a, ERC9b: Industrial use of substances in closed systems, Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Viscosity, dynamic	1.2 mPas at 20 °C

Amount used

Annual amount	10,000,000 kg
---------------	---------------

Frequency and duration of use

Continuous exposure	The likelihood that workers or the general public or the environment are exposed to the substance under normal or reasonably foreseeable conditions of use is negligible.
---------------------	---

Technical conditions and measures / Organizational measures

Remarks	: No specific measures identified.
---------	------------------------------------

Conditions and measures related to municipal sewage treatment plant

Percentage removed from waste eater	: 90 %
Sludge Treatment	: Can be landfilled or incinerated, when in compliance with local regulations.

Conditions and measures related to external treatment of waste for disposal

Disposal methods	: Dispose of as hazardous waste in compliance with local and national regulations.
------------------	--

2.2 Contributing scenario controlling worker exposure:

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
 Physical Form (at time of use) : Liquid substance
 Vapour pressure : 57.3 hPa
 Process Temperature : 20 °C

Amount used

Remarks : Not applicable.

Human factors not influenced by risk management

Dermal exposure : Palms of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/Indoor : Indoor, Outdoor
 Other Operational Conditions affecting worker exposure : Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenario

Risk Management Measures

: Handle substance within a closed system., Store substance within a closed system. Use suitable eye protection.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC7 ERC9a ERC9b	ECETOC TRA		Fresh water		0.0107 mg/L	0.0111
			Marine water		0.001 mg/L	0.00127
			Soil		0.0002 mg/kg dwt	0.000317

Health

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR
PROC2Q	ECETOC TRA, EUSES	Inhalation		20 ppm	0.040439
				38.4167 mg/m ³	0.040439
		Skin contact		1.7143 mg/kg/day	0.01106

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Sectors of end-use	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems
Environmental Release Categories	ERC7, ERC9a, ERC9b: Industrial use of substances in closed systems, Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure:

ERC7, ERC9a, ERC9b: Industrial use of substances in closed systems, Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Viscosity, dynamic	1.2 mPas at 20 °C

Amount used

Annual amount	10,000,000 kg
---------------	---------------

Frequency and duration of use

Continuous exposure	The likelihood that workers or the general public or the environment are exposed to the substance under normal or reasonably foreseeable conditions of use is negligible.
---------------------	---

Technical conditions and measures / Organizational measures

Remarks	: No specific measures identified.
---------	------------------------------------

Conditions and measures related to municipal sewage treatment plant

Percentage removed from waste eater	: 90 %
Sludge Treatment	: Can be landfilled or incinerated, when in compliance with local regulations.

Conditions and measures related to external treatment of waste for disposal

Disposal methods	: Dispose of as hazardous waste in compliance with local and national regulations.
------------------	--

2.2 Contributing scenario controlling worker exposure:

ANNEX TO SAFETY DATA SHEET: ETHANOL BLEND - 1DA

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
 Physical Form (at time of use) : Liquid substance
 Vapour pressure : 57.3 hPa
 Process Temperature : 20 °C

Amount used

Remarks : Not applicable.

Human factors not influenced by risk management

Dermal exposure : Palms of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/Indoor : Indoor, Outdoor
 Other Operational Conditions affecting worker exposure : Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenario

Risk Management Measures

: Handle substance within a closed system., Store substance within a closed system. Use suitable eye protection.

3. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC7 ERC9a ERC9b	ECETOC TRA		Fresh water		0.0107 mg/L	0.0111
			Marine water		0.001 mg/L	0.00127
			Soil		0.0002 mg/kg dwt	0.000317

Health

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR
PROC2Q	ECETOC TRA, EUSES	Inhalation		20 ppm	0.040439
				38.4167 mg/m ³	0.040439
		Skin contact		1.7143 mg/kg/day	0.01106